



TECHNICAL DATA SHEET



Opaque **ELYONDA** straight and ribbed sheet is the registered trademark made of fibreglass reinforced polyester and loaded with alluminium oxide mineral. The laminates produced in the profiles **R146**, **R153 R177** and **R627** are protected on the external surface with isophthalic gel-coat (which gives high abrasion resistance at the laminates) and are suitable to meet any requirement for roof covering (particularly industrial and agricultural) and vertical closing.

ELYONDA is produced in conformity to the following characteristics and technical norms:

Reinforcement:	Fibreglass	
% fibreglass	≥ 20%	
Charge:	Alluminium oxide mineral	
Weight:	3,200 kg/m ² ; 3,500 kg/m ² (tolerance ± 5%) On request: 4,200 kg/m ²	
Superficial protection:	Isophthalic gel-coat, U.V. stabilised	
Colours:	Light Grey, Brick Red, Green. On request: Charcoal Grey, Coral Red, Blue	
Exercise temperature:	-60 °C ÷ +140 °C	
Self-ignition temperature:	ca. 400 ℃	
Reaction to fire:	Italian Class 1 (D.M. 26/06/1984 and D.M. 03/09/01) (Type-approval doc. n° MI380A60D100007 16/06/03 - exp.2018)	
Thermal conductivity (λ) :	0,22 W/mK (ASTM C177)	
Heat transmission (U):	220 W/m ² K (thickness 1 mm)	
Thermal linear expansion:	2 - 2,5 x 10 ⁻⁵ cm/cm °C	
Light transmission:	100% opaque	
Water absorption:	0,2% after 48 hr of dipping	
Resistance to chemical agents:	Corrugated laminates are not altered by the following acids in the listed solutions depending on their concentration and on a testing temperature ranging from 30° to 50° C.	
	Acetic acid ⇒ 10%	Sulphuric acid \Rightarrow 30%
	Chlorohydric acid \Rightarrow 35%	Ethyl alcohol \Rightarrow 95%
	Nitric acid ⇒ 10%	Benzol ⇒ 30%
	Ammonia conc. \Rightarrow 30%	Ammonium chloride $\Rightarrow 50\%$

The information contained in this technical data sheet is based on present information and experiences and is correct and precise, as far as we know. The information has no meaning of quality guarantee as the employment conditions are not under our direct control.

Rev.: 2 02/14 Pag. 1 of 2


Brianza Plastica S.p.A.


A Company with a Quality Management System UNI EN ISO 9001:2008 certified (certif. Nº 106 SQP-IIP)


Via Rivera, 50, 20841 Carate Brianza (MB) • Tel. 0362.91601 • Fax 0362. 990457 http://: www.brianzaplastica.it • e-mail: info@brianzaplastica.it Co. Cap. Euro 3,000,000 fully paid-up • MB Company Registration N° 3960 REA/MB Registration N° 602163 • Tax N° 00865040158 • VAT N° IT00698250966




PROFILES











EYONDA

RIDGES

R104





COLOURS









*Coral Red



*Blue



*On request. Coral Red only for R627

The information contained in this technical data sheet is based on present information and experiences and is correct and precise, as far as we know. The information has no meaning of quality guarantee as the employment conditions are not under our direct control.

Rev.: 2 02/14 Pag. 2 of 2

Brianza Plastica S.p.A.